

SAFETY DATA SHEET

LIQUID GOLD

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME LIQUID GOLD

2 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking. Harmful: may cause lung damage if swallowed. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R65. N;R51/53. R10, R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|--------------|-----------|------------|---------|----------------------------|
| WHITE SPIRIT | 265-185-4 | 64742-82-1 | 10-30% | Xn;R65. N;R51/53. R10,R66. |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Remove to fresh air.

INGESTION

DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Rinse with water.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam, carbon dioxide or dry powder.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Prevent eye and skin contact. Avoid inhalation.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains or rivers. Prevent liquid entering water course.

7 HANDLING AND STORAGE

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

LIQUID GOLD

| Name | Std | TWA - 8 hrs | | STEL - 15 min | | Notes |
|--------------|-----|-------------|-----------|---------------|--|-------|
| WHITE SPIRIT | WEL | | 600 mg/m3 | | | |

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Well-ventilated area.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear eye protection if splashes to the eye are likely to occur.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|---------------|------------------|---------------------|
| APPEARANCE | Clear liquid | | |
| COLOUR | pale straw | | |
| ODOUR | Almond. | | |
| RELATIVE DENSITY | 0.831 @ 25 °c | FLASH POINT (°C) | 58 CC (Closed cup). |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system.

INGESTION

Harmful: may cause lung damage if swallowed.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

May cause mild irritation or discomfort.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of in accordance with local authority requirements.

14 TRANSPORT INFORMATION

LIQUID GOLD



| | | | |
|-----------------------------|---|-------------------------|-----|
| UK ROAD CLASS | 3 | | |
| PROPER SHIPPING NAME | FLAMMABLE LIQUID NOS (petroleum distillate) | | |
| UN NO. ROAD | 1993 | UK ROAD PACK GR. | III |
| ADR CLASS | Class 3: Flammable liquids. | ADR PACK GROUP | III |
| MARINE POLLUTANT | No. | | |

15 REGULATORY INFORMATION

LABELLING



Harmful



Dangerous for the environment

CONTAINS

WHITE SPIRIT

RISK PHRASES

| | |
|--------|---|
| R10 | Flammable. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R65 | Harmful: may cause lung damage if swallowed. |

SAFETY PHRASES

| | |
|--------|--|
| S2 | Keep out of the reach of children |
| S13 | Keep away from food, drink and animal feeding stuffs. |
| S29/56 | Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. |
| S37 | Wear suitable gloves. |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |
| S51 | Use only in well-ventilated areas. |
| S61 | Avoid release to the environment. Refer to special instructions/safety data sheets. |

16 OTHER INFORMATION

| | |
|-------------------------------------|----------|
| REV. NO./REPL. SDS GENERATED | 1 |
| SDS NO. | B0100 |
| DATE | 03/08/09 |

RISK PHRASES IN FULL

| | |
|--------|---|
| R10 | Flammable. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.