

# SAFETY DATA SHEET

## STAINLESS STEEL CLEANER

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**PRODUCT NAME** STAINLESS STEEL CLEANER  
**PRODUCT NO.** A5715

### 2 HAZARDS IDENTIFICATION

Extremely flammable.

**CLASSIFICATION** F+;R12.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
HYDROCARBON PROPELLANT	649-202-00-6	68476-85-7	10-30%	F+;R12.
ISOPARAFFINIC HYDROCARBON		90622-57-04	5-10%	Xn;R65. R10,R53,R66.

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

Aerosol propelled by liquefied petroleum gas.

### 4 FIRST-AID MEASURES

#### INHALATION

If inhalation of vapours causes irritation or drowsiness, remove to fresh air.

#### INGESTION

Rinse mouth thoroughly. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Rinse the skin immediately with lots of water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Rinse the eye with water immediately. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Foam, carbon dioxide or dry powder.

#### SPECIAL FIRE FIGHTING PROCEDURES

Breathing apparatus should be worn if exposure to fumes is likely. Use water to keep fire exposed containers cool and disperse vapours.

#### UNUSUAL FIRE & EXPLOSION HAZARDS

Possible risk of can rupture when exposed to fire/high temps. Contents of aerosol will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb material from ruptured or leaking containers onto an inert material. Transfer to suitable container for subsequent disposal.



# STAINLESS STEEL CLEANER



<b>UN NO. ROAD</b>	1950	<b>ADR CLASS</b>	Class 2.1: Flammable gases.
<b>UN NO. SEA</b>	1950	<b>UN NO. AIR</b>	1950

## 15 REGULATORY INFORMATION

**LABELLING**



Extremely Flammable

**RISK PHRASES**

R12 Extremely flammable.

**SAFETY PHRASES**

- S2 Keep out of the reach of children
- S9 Keep container in a well-ventilated place.
- S16 Keep away from sources of ignition - No smoking.
- S35 This material and its container must be disposed of in a safe way.
- S51 Use only in well-ventilated areas.

**DETERGENT LABELLING**

- 15-30% Aliphatic hydrocarbons
- < 5% Anionic surfactants
- Non-ionic surfactants
- Contains SODIUM BENZOATE

## 16 OTHER INFORMATION

<b>REVISION DATE</b>	15/10/07
<b>DATE</b>	26-10-2004

**RISK PHRASES IN FULL**

- R10 Flammable.
- R12 Extremely flammable.
- R53 May cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.

**DISCLAIMER**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.